# NSN 5930-00-168-8015

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-168-8015

## **Thread Class:**

2a single mounting facility

## Thread Length:

0.218 inches single mounting facility

## Width Between Flats:

0.064 inches single actuator

#### **Overall Length:**

1.976 inches

#### First Flat Length:

0.093 inches single actuator

#### Shaft Diameter:

0.125 inches single actuator

### Shaft Length:

0.328 inches single actuator

### **Overall Diameter:**

0.720 inches

### Individual Section Quantity:

5

### Switch Contact Basic Design:

Nonpile-up nonsymmetrical

### **Pole Quantity:**

1 each section rear

### Throw Quantity:

10 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Features Provided:**

Metallic inclosure

### Thread Size:

0.250 inches single mounting facility

### Contact Voltage Rating In Volts:

115.0 dc at sea level

### Switch Actuator Indexing Position Quantity:

10 single actuator

### Shaft Type:

Round, parallel flatted single actuator

# Criticality Code Justification:

Feat

# Terminal Type:

Tab, solder lug

### **Contact Switching Action:**

Breaks before makes each section rear

# NSN 5930-00-168-8015

Rotary Switch - Page 2 of 2



## Switch Actuator Positioning Increment:

36.0 degrees single actuator

#### **Contact Load Current Rating:**

250.0 milliamperes resistive load dc at sea level

#### **Special Features:**

Weapons system essential

## Style Designator:

Tap, circular, bushing mount

#### **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

# Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A052b0