NSN 5930-00-168-9189

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-168-9189

Threa	ad I	end	ath:
11116	au L	.6111	4111.

0.250 inches single mounting facility

Overall Length:

1.910 inches

Overall Height:

1.875 inches

Overall Width:

1.609 inches

First Flat Length:

0.188 inches single actuator

Flat Height:

0.156 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.500 inches single actuator

Overall Diameter:

3.218 inches

Nonturn Device Radius:

0.531 inches at 3: 00 o'clock

Individual Section Quantity:

3

Nonturn Device Type:

Tab at 3: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Mounting Method:

Threaded bushing single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

35.0 degrees from contact position 1 single actuator

Switch Actuator Indexing Position Quantity:

18 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

NSN 5930-00-168-9189

Rotary Switch - Page 2 of 2



Sty					

Circular wafer, bushing mount

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0