

View Online at <https://aerobasegroup.com/nsn/5930-00-170-3920>

Inside Diameter:

0.125 inches all connections

Overall Length:

1.812 inches

Overall Width:

Between 4.594 inches and 4.656 inches

Body Diameter:

3.500 inches

Body Length:

1.812 inches

Unthreaded Mounting Hole Diameter:

0.219 inches

Distance Between Mounting Facility Centers:

Between 4.219 inches and 4.281 inches

Pressure Switch Type:

Differential

Operating Temperature Rating:

Between -54.0 degrees celsius and 55.0 degrees celsius

Mounting Method:

Flange and unthreaded hole

Contact Action Stimulus:

Increase

Proof Pressure:

5.00 pounds per square inch

Thread Size:

0.125 inches all pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Screw

Contact Load Current Rating:

15.0 amperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+1.40 to 5.00 actuation point inches of water

Contact Adjustment Type:

External actuation point pointer

Contact Voltage Rating In Volts:

240.0 ac at sea level second voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Gas or liquid

Style Designator:

Cylindrical w/mounting lugs

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0