

View Online at <https://aerobasegroup.com/nsn/5930-00-170-4127>

**Thread Class:**

2a

**Body Style:**

Bushing mounted

**Bushing Length:**

0.310 inches

**Body Length:**

0.990 inches

**Body Width:**

0.780 inches

**Body Height:**

0.670 inches

**Actuator Diameter:**

0.500 inches

**Actuator Height:**

0.430 inches

**Actuator Color:**

Gray single actuator

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Uninclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

24

**Thread Size:**

0.625 inches

**Nonpile-up Contact Arrangement:**

3 two circuit, double break/double make, one position momentary single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive dc and 5.000 amperes inductive dc and 3.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

12 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0