## NSN 5930-00-172-8060

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-172-8060

Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.875 inches
Body Length:
1.094 inches
Body Width:
0.406 inches
Body Height:
0.625 inches
Unthreaded Mounting Hole Diameter:
0.114 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.406 inches
Actuator Length:
0.812 inches
Actuator Style:
Roller arm
Actuator Free Position Height:
0.400 inches
Actuator Roller Diameter:
0.375 inches
Actuator Roller Width:
0.188 inches
Maximum Voltage Rating In Volts:
250.0 ac
Inclosure Type:
Fully enclosed
Mounting Method:
Threaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
175.0 grams
Switch Actuating Force:
285.0 grams
Actuator Movement:
Between 0.047 pretravel inches and 0.040 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:** 

10.000 amperes resistive ac

## NSN 5930-00-172-8060

Sensitive Switch - Page 2 of 2



Terminal '	Type And	Quantity:
ı errillinar	I VDE AIIU	Qualitity.

3 tab, solder lug

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0