

View Online at <https://aerobasegroup.com/nsn/5930-00-172-8060>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.875 inches

**Body Length:**

1.094 inches

**Body Width:**

0.406 inches

**Body Height:**

0.625 inches

**Unthreaded Mounting Hole Diameter:**

0.114 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.406 inches

**Actuator Length:**

0.812 inches

**Actuator Style:**

Roller arm

**Actuator Free Position Height:**

0.400 inches

**Actuator Roller Diameter:**

0.375 inches

**Actuator Roller Width:**

0.188 inches

**Maximum Voltage Rating In Volts:**

250.0 ac

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

175.0 grams

**Switch Actuating Force:**

285.0 grams

**Actuator Movement:**

Between 0.047 pretravel inches and 0.040 overtravel inches and 0.010 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

10.000 amperes resistive ac

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0