# NSN 5930-00-172-9176

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-172-9176

# **Shaft Length:**

1.344 inches single actuator

#### **Overall Diameter:**

3.750 inches

# **Unthreaded Mounting Hole Diameter:**

0.257 inches single mounting facility

# **Individual Section Quantity:**

12

#### **Longest Horizontal Distance Between Mounting Centers:**

2.297 inches single mounting facility

#### **Longest Vertical Distance Between Mounting Centers:**

2.297 inches single mounting facility

#### **Switch Contact Basic Design:**

Nonpile-up symmetrical

#### **Pole Quantity:**

1 each section front

#### **Throw Quantity:**

7 each section front

#### **Features Provided:**

Variable resistor and actuator knob

# Thready Qty Per Inch (tpi):

24 single mounting facility

#### **Thread Size:**

0.190 inches single mounting facility

# **Contact Voltage Rating In Volts:**

125.0 dc at sea level

# **Mounting Facility Pattern:**

Four position rectangular single mounting facility

#### **Switch Actuator Indexing Position Quantity:**

8 single actuator

# **Shaft Type:**

Rectangular/square, threaded hole single actuator

# **Square Shaft Size:**

0.250 inches single actuator

# **Terminal Type:**

Tab w/screw

# **Contact Switching Action:**

Breaks before makes each section front

# **Switch Actuator Positioning Increment:**

45.0 degrees single actuator

# **Switch Actuator Stop Device Type:**

Adjustable stop single actuator

# NSN 5930-00-172-9176

Rotary Switch - Page 2 of 2



Contact Load Current Rating
-----------------------------

5.0 amperes resistive load dc at sea level

**Thread Series Designator:** 

Unc single mounting facility

**Reference Number Differentiating Characteristics:** 

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0