

View Online at <https://aerobasegroup.com/nsn/5930-00-173-9890>

**Thread Class:**

3a single pressure connection

**Thread Length:**

0.282 inches single pressure connection

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

4.400 inches

**Outside Diameter:**

0.438 inches single connection

**Body Diameter:**

1.670 inches

**Body Length:**

2.540 inches

**Overall Diameter:**

1.850 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

**Mounting Method:**

Clamp

**Features Provided:**

Hermetically sealed case

**Thready Qty Per Inch (tpi):**

20 single pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

800.00 pounds per square inch

**Thread Size:**

0.438 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary

**Sensing Element Burst Pressure:**

1200.00 pounds per square inch

**Terminal Type:**

Connector, receptacle

**Contact Load Current Rating:**

10.0 amperes resistive load single voltage and 10.0 amperes inductive load single voltage and 5.0 amperes lamp load single voltage

**Contact Adjustability:**

Deactuation point not adjustable and actuation point not adjustable

**Contact Stimulus Rating:**

85.00 actuation point pounds per square inch and 60.00 deactuation point pounds per square inch and 25.00 differential point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical

**Test Data Document:**

81349-mil-s-9395 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf single pressure connection

**Specification Data:**

81349-mil-s-9395/10 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0