NSN 5930-00-174-1516

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-174-1516

Body Style:

Bushing mounted

Hazardous Locations/environmental Protection:

Dustproof and dustproof and watertight

Body Diameter:

1.000 inches

Bushing Length:

1.000 inches

Body Length:

1.000 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.250 inches

.

Actuator Height:

0.375 inches

Actuator Free Position Height:

1.375 inches

Maximum Voltage Rating In Volts:

28.0 dc

Inclosure Type:

Hermetically sealed

Features Provided:

Actuator seal

Thread Size:

0.625 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, one position momentary single switch unit

Switch Release Force:

80.0 ounces

Switch Actuating Force:

143.0 ounces

Actuator Movement:

Between 0.070 pretravel inches and 0.250 overtravel inches and 0.035 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 3.000 amperes inductive dc and 6.000 amperes motor dc

Thread Series Designator:

Unef

Terminal Type And Quantity:

6 wire lead

NSN 5930-00-174-1516

Sensitive Switch - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A053a0

