## NSN 5930-00-174-1516

**Hazardous Locations/environmental Protection:** 

Sensitive Switch - Page 1 of 2

Dustproof and dustproof and watertight

**Body Style:** 

Bushing mounted



View Online at https://aerobasegroup.com/nsn/5930-00-174-1516

Body Diameter:
1.000 inches
Bushing Length:
1.000 inches
Body Length:
1.000 inches
Switch Actuator Quantity:
1
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.375 inches
Actuator Free Position Height:
1.375 inches
Maximum Voltage Rating In Volts:
28.0 dc
Inclosure Type:
Hermetically sealed
Features Provided:
Actuator seal
Thread Size:
0.625 inches
Nonpile-up Contact Arrangement:
2 pole, double throw, one position momentary single switch unit
Switch Release Force:
80.0 ounces
Switch Actuating Force:
143.0 ounces
Actuator Movement:
Between 0.070 pretravel inches and 0.250 overtravel inches and 0.035 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes resistive dc and 3.000 amperes inductive dc and 6.000 amperes motor dc
Thread Series Designator:
Unef
Terminal Type And Quantity:
6 wire lead

## NSN 5930-00-174-1516

Sensitive Switch - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0