## NSN 5930-00-174-5893

Sensitive Switch - Page 1 of 2

N/a



View Online at https://aerobasegroup.com/nsn/5930-00-174-5893

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
4.907 inches
Overall Height:
7.125 inches
Actuator Length:
4.625 inches
Actuator Style:
Adjustable arm
Actuator Diameter:
0.375 inches
Actuator Height:
0.953 inches
Actuator Width:
7.688 inches
Housing Length:
2.875 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
6.188 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
2.125 inches
Maximum Voltage Rating In Volts:
575.0 ac and 125.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Actuator Movement:
10.0 pretravel degrees and 2.0 overtravel degrees and 5.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes resistive ac
Terminal Type And Quantity:
3 screw
Shelf Life:

## NSN 5930-00-174-5893

Sensitive Switch - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A053a0