NSN 5930-00-174-5893

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-174-5893

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

4.907 inches

Overall Height:

7.125 inches

Actuator Length:

4.625 inches

Actuator Style:

Adjustable arm

Actuator Diameter:

0.375 inches

Actuator Height:

0.953 inches

Actuator Width:

7.688 inches

Housing Length:

2.875 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Height:

6.188 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.125 inches

Maximum Voltage Rating In Volts:

575.0 ac and 125.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Actuator Movement:

10.0 pretravel degrees and 2.0 overtravel degrees and 5.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes resistive ac

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

NSN 5930-00-174-5893

Sensitive Switch - Page 2 of 2

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A053a0

