

View Online at <https://aerobasegroup.com/nsn/5930-00-174-5897>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

11.625 inches

Overall Height:

2.875 inches

Overall Width:

7.000 inches

Longest Horizontal Distance Between Mounting Centers:

4.688 inches

Longest Vertical Distance Between Mounting Centers:

3.000 inches

Pressure Switch Type:

Gage

Mounting Method:

Bracket

Thready Qty Per Inch (tpi):

18 single pressure connection

Contact Action Stimulus:

Increase

Thread Size:

0.250 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

2.7 amperes resistive load first voltage and 1.0 amperes resistive load first voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+500.00 to 3000.00 actuation point pounds per square inch

Contact Adjustment Type:

Internal actuation point screw with scale

Contact Voltage Rating In Volts:

550.0 dc at sea level third voltage

Frequency In Hertz:

60.0 single voltage

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0