

View Online at <https://aerobasegroup.com/nsn/5930-00-174-5897>

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

11.625 inches

**Overall Height:**

2.875 inches

**Overall Width:**

7.000 inches

**Longest Horizontal Distance Between Mounting Centers:**

4.688 inches

**Longest Vertical Distance Between Mounting Centers:**

3.000 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Bracket

**Thready Qty Per Inch (tpi):**

18 single pressure connection

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.250 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

2.7 amperes resistive load first voltage and 1.0 amperes resistive load first voltage

**Contact Adjustability:**

Actuation point adjustable

**Contact Adjustment Range:**

+500.00 to 3000.00 actuation point pounds per square inch

**Contact Adjustment Type:**

Internal actuation point screw with scale

**Contact Voltage Rating In Volts:**

550.0 dc at sea level third voltage

**Frequency In Hertz:**

60.0 single voltage

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0