NSN 5930-00-174-5898

Rotary Switch - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5950-00-174-5696
Hazardous Locations/environmental Protection:
Watertight
Overall Height:
10.125 inches
Overall Width:
6.562 inches
Shaft Length:
0.750 inches single actuator
Unthreaded Mounting Hole Diameter:
0.531 inches single mounting facility
Individual Section Quantity:
1
Knob Manufacturer Code:
42337
Knob Manufacturer Part Number:
D1386
Longest Horizontal Distance Between Mounting Centers:
1.000 inches single mounting facility
Shortest Horizontal Distance Between Mounting Centers:
1.062 inches single mounting facility
Longest Vertical Distance Between Mounting Centers:
6.188 inches single mounting facility
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section front
Throw Quantity:
1 single section front
Mounting Method:
Base single mounting facility
Features Provided:
Actuator knob and metallic inclosure
Contact Voltage Rating In Volts:
500.0 dc at sea level
Mounting Facility Pattern:
Isosceles triangle single mounting facility
Switch Actuator Indexing Position Quantity:
2 single actuator
Shaft Type:
Rectangular/square, threaded hole single actuator
Terminal Type:

Tab w/screw

NSN 5930-00-174-5898

Rotary Switch - Page 2 of 2



Con	tact	Swit	chino	ı Acti	on:
OUL	ıavı	OWIL	CHILL	ı Actı	vii.

Breaks before makes single section front

Switch Actuator Positioning Increment:

20.0 degrees single actuator

Contact Load Current Rating:

30.0 amperes resistive load dc at sea level

Test Data Document:

81349-mil-c-2212 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0