NSN 5930-00-175-4358

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-175-4358

| Body Style: | | | | |
|---|--|--|--|--|
| Bushing mounted | | | | |
| Overall Length: | | | | |
| 0.562 inches | | | | |
| Overall Height: | | | | |
| 2.355 inches | | | | |
| Overall Width: | | | | |
| 0.562 inches | | | | |
| Body Diameter: | | | | |
| 0.562 inches | | | | |
| Bushing Length: | | | | |
| 0.425 inches | | | | |
| Body Length: | | | | |
| 1.160 inches | | | | |
| Actuator Length: | | | | |
| 0.500 inches | | | | |
| Actuator Style: | | | | |
| Rectangular | | | | |
| Actuator Height: | | | | |
| 0.505 inches | | | | |
| Actuator Width: | | | | |
| 0.500 inches | | | | |
| Actuator Color: | | | | |
| Black single actuator | | | | |
| Illuminated Actuator Color: | | | | |
| White single actuator | | | | |
| Actuator Inscription: | | | | |
| 6 single actuator | | | | |
| Maximum Voltage Rating In Volts: | | | | |
| 28.0 dc | | | | |
| Inclosure Type: | | | | |
| Fully enclosed | | | | |
| Mounting Method: | | | | |
| Unthreaded bushing | | | | |
| Features Provided: | | | | |
| Rfi shielding | | | | |
| Nonpile-up Contact Arrangement: | | | | |
| 1 pole, double throw, one position momentary single switch unit | | | | |
| Contact Load Current Rating At Maximum Rated Voltage: | | | | |
| 1.000 amperes resistive dc and 0.500 amperes inductive dc | | | | |

Special Features:

Includes two lamp terminals

NSN 5930-00-175-4358

Push Switch - Page 2 of 2



| Precious | Material | ∆nd l | Location: |
|----------|------------|-------|------------|
| riecious | ivialeriai | Allu | LUCALIUII. |

Contacts gold

Terminal Type And Quantity:

2 tab, solder lug and 3 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0