## NSN 5930-00-175-4522

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-175-4522

**Thread Class:** 2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

3.625 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

0.500 inches single actuator

**Overall Diameter:** 

1.500 inches

**Individual Section Quantity:** 

**End Application:** 

Forrestal class cv

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section rear

**Throw Quantity:** 

2 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Features Provided:** 

Variable resistor

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section rear

**Switch Actuator Positioning Increment:** 

30.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

## NSN 5930-00-175-4522

Rotary Switch - Page 2 of 2



Contact Load Current Ratin
----------------------------

1.0 amperes resistive load ac at sea level

**Precious Material And Location:** 

Contacts silver

**Precious Material:** 

Silver

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

**Demilitarization:** 

No

Fiig:

A052b0