

View Online at <https://aerobasegroup.com/nsn/5930-00-175-4588>

Hazardous Locations/environmental Protection:

Watertight

Overall Length:

5.750 inches

Overall Height:

2.812 inches

Overall Width:

2.094 inches

Body Length:

4.750 inches

Distance Between Mounting Facility Centers:

5.250 inches

Capillary Tube Length:

120.000 inches

Bulb Length:

8.625 inches

Bulb Diameter:

0.688 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

245.0 degrees fahrenheit

Mounting Method:

Bracket

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, momentary action

Terminal Type:

Tab w/screw

Contact Load Current Rating:

9.6 amperes resistive load third voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+140.00 to 215.00 actuation point degrees fahrenheit and +135.00/+210.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 dc at sea level fourth voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0