NSN 5930-00-175-4588

Thermostatic Switch - Page 1 of 2

Contact Voltage Rating In Volts: 550.0 dc at sea level fourth voltage



View Online at https://aerobasegroup.com/nsn/5930-00-175-4588

Hazardous Locations/environmental Protection:
Watertight
Overall Length:
5.750 inches
Overall Height:
2.812 inches
Overall Width:
2.094 inches
Body Length:
4.750 inches
Distance Between Mounting Facility Centers:
5.250 inches
Capillary Tube Length:
120.000 inches
Bulb Length:
8.625 inches
Bulb Diameter:
0.688 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
245.0 degrees fahrenheit
Mounting Method:
Bracket
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Two position in-line
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Tab w/screw
Contact Load Current Rating:
9.6 amperes resistive load third voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+140.00 to 215.00 actuation point degrees fahrenheit and +135.00/+210.00 deactuation point degrees fahrenheit
Contact Adjustment Type:
External deactuation point screw and external actuation point screw

NSN 5930-00-175-4588 Thermostatic Switch - Page 2 of 2



Media For Which Designed:
Gas or liquid
Style Designator:
Rectangular
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0