

View Online at <https://aerobasegroup.com/nsn/5930-00-175-5903>

**Body Style:**

Hole mounted

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.188 inches

**Body Length:**

0.500 inches

**Body Width:**

0.200 inches

**Body Height:**

0.350 inches

**Unthreaded Mounting Hole Diameter:**

0.090 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.063 inches

**Actuator Height:**

0.050 inches

**Actuator Free Position Height:**

0.340 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**End Application:**

F-5, f-16, t-38

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

1.0 ounces

**Criticality Code Justification:**

Feat

**Switch Actuating Force:**

5.0 ounces

**Actuator Movement:**

Between 0.020 pretravel inches and 0.004 overtravel inches and 0.003 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

**Special Features:**

Weapon system essential

**Terminal Type And Quantity:**

3 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0