

View Online at <https://aerobasegroup.com/nsn/5930-00-175-9694>

Thread Class:

2b single mounting facility

Overall Length:

4.375 inches

Overall Height:

2.000 inches

Overall Width:

2.000 inches

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.906 inches single actuator and 0.968 inches single actuator

Distance Between Mounting Facility Centers:

1.370 inches single mounting facility and 1.380 inches single mounting facility

Individual Section Quantity:

2

Operating Temperature Range:

-55.0/+85.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section rear

Throw Quantity:

12 each section rear

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Variable resistor

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

12 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks 2nd section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

2.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts and wiper arms silver

Precious Material:

Silver

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0