NSN 5930-00-177-2132

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-177-2132

| Body Style: |
|--|
| Bushing mount |
| Hazardous Locations/environmental Protection: |
| Dustproof |
| Bushing Length: |
| 0.468 inches |
| Body Length: |
| 0.492 inches |
| Body Width: |
| 0.453 inches |
| Body Height: |
| 0.482 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.187 inches |
| Actuator Height: |
| 0.413 inches |
| Actuator Position-action Relationship: |
| Up position maintained and down position maintained and center position maintained |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 30.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 2 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 2.000 amperes inductive dc and 3.000 amperes resistive ac |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 6 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5930-00-177-2132

Toggle Switch - Page 2 of 2



Demilitarization:

No

Fiig:

A053a0