

View Online at <https://aerobasegroup.com/nsn/5930-00-177-2303>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Weatherproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.375 inches

Body Length:

0.789 inches

Body Width:

0.250 inches

Unthreaded Mounting Hole Diameter:

0.091 inches

Actuator Length:

0.296 inches

Actuator Style:

Leaf

Actuator Free Position Height:

0.360 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Hermetically sealed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

1.0 ounces

Switch Actuating Force:

7.0 ounces

Actuator Movement:

Between 0.030 pretravel inches and 0.003 overtravel inches and 0.006 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.000 amperes inductive dc and 4.000 amperes resistive ac and 2.000 amperes inductive ac

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0