

View Online at <https://aerobasegroup.com/nsn/5930-00-177-7115>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Shock resistant and vibration resistant and weatherproof

Overall Length:

Between 0.409 inches and 0.471 inches

Overall Height:

Between 0.305 inches and 0.335 inches

Overall Width:

Between 0.450 inches and 0.468 inches

Body Diameter:

Between 0.305 inches and 0.335 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

Between 0.065 inches and 0.075 inches

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

Between 21.0 ounces and 30.0 ounces

Actuator Movement:

Between 0.008 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

7.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

Special Features:

Case hermetically sealed; class 5 per mil-s- 8805

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0