

View Online at <https://aerobasegroup.com/nsn/5930-00-177-7115>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Shock resistant and vibration resistant and weatherproof

**Overall Length:**

Between 0.409 inches and 0.471 inches

**Overall Height:**

Between 0.305 inches and 0.335 inches

**Overall Width:**

Between 0.450 inches and 0.468 inches

**Body Diameter:**

Between 0.305 inches and 0.335 inches

**Case Material:**

Metal

**Actuator Style:**

Round

**Actuator Diameter:**

Between 0.065 inches and 0.075 inches

**Maximum Voltage Rating In Volts:**

115.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, double throw, one position momentary single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 21.0 ounces and 30.0 ounces

**Actuator Movement:**

Between 0.008 pretravel inches and 0.003 overtravel inches and 0.005 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

7.000 amperes resistive dc and 3.000 amperes inductive dc and 1.000 amperes lamp dc and 5.000 amperes resistive ac and 3.000 amperes inductive ac and 2.000 amperes lamp ac

**Special Features:**

Case hermetically sealed; class 5 per mil-s- 8805

**Terminal Type And Quantity:**

3 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0