## NSN 5930-00-177-9383

Flow Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-177-9383

Thread Class:
3b all threaded hole
Overall Length:
4.120 inches
Overall Height:
2.000 inches
Overall Width:
1.250 inches
Body Length:
4.120 inches
Unthreaded Mounting Hole Diameter:
0.187 inches
Longest Horizontal Distance Between Mounting Centers:
2.700 inches
Longest Vertical Distance Between Mounting Centers:
1.600 inches
Operating Tempurature Rating:
Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit
Mounting Method:
Threaded hole
Contact Action Stimulus:
Increase
Thread Size:
0.750 inches all threaded hole
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Wire lead
Contact Load Current Rating:
500.0 milliamperes resistive load third voltage
Contact Adjustability:
Actuation point adjustable
Contact Adjustment Range:
+0.20 to 15.00 actuation point gallons per minute
Contact Adjustment Type:
External actuation point screw
Contact Voltage Rating In Volts:

Frequency In Hertz:

6.0 dc at sea level second voltage

60.0 first voltage

## **NSN 5930-00-177-9383** Flow Switch - Page 2 of 2



Media For Which Designed:
Liquid
Style Designator:
Rectangular
Thread Series Designator:
Unf all threaded hole
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A048b0