

View Online at <https://aerobasegroup.com/nsn/5930-00-183-6539>

**Body Style:**

Bushing/hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Bushing Length:**

0.570 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

0.928 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.330 inches

**Actuator Height:**

0.859 inches

**Actuator Free Position Height:**

1.489 inches

**Maximum Voltage Rating In Volts:**

480.0 ac and 240.0 dc

**Inclosure Type:**

Fully enclosed

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 9.0 ounces and 13.0 ounces

**Actuator Movement:**

0.219 overtravel inches and 0.002 differential inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

3 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0