NSN 5930-00-183-6539

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-183-6539

Bushing/hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Bushing Length:
0.570 inches
Body Length:
1.940 inches
Body Width:
0.687 inches
Body Height:
0.928 inches
Unthreaded Mounting Hole Diameter:
0.140 inches
Actuator Style:
Round
Actuator Diameter:
0.330 inches
Actuator Height:
0.859 inches
Actuator Free Position Height:
1.489 inches
Maximum Voltage Rating In Volts:
480.0 ac and 240.0 dc
Inclosure Type:
Fully enclosed
Features Provided:
Actuator seal
Thready Qty Per Inch (tpi):
32
Thread Size:
0.469 inches
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 9.0 ounces and 13.0 ounces
Actuator Movement:

0.219 overtravel inches and 0.002 differential inches

NSN 5930-00-183-6539

Sensitive Switch - Page 2 of 2



Contact Load Current Rating At Maximum Rated Voltage:

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0