NSN 5930-00-185-5141

Thermostatic Switch - Page 1 of 2

Thread Class:



View Online at https://aerobasegroup.com/nsn/5930-00-185-5141

| 2b all threaded hole |
|---|
| Hazardous Locations/environmental Protection: |
| Dusttight |
| Overall Length: |
| 3.344 inches |
| Overall Height: |
| 3.167 inches |
| Overall Width: |
| 1.875 inches |
| Body Height: |
| 2.656 inches |
| Distance Between Mounting Facility Centers: |
| 1.000 inches |
| Capillary Tube Length: |
| 74.500 inches |
| Bulb Length: |
| 1.500 inches |
| Bulb Diameter: |
| 0.375 inches |
| Tempurature Sensing Element Type: |
| Capillary tube-bulb |
| Operating Tempurature Rating: |
| 85.0 degrees fahrenheit |
| Mounting Method: |
| Bracket and threaded hole |
| Thready Qty Per Inch (tpi): |
| 32 all threaded hole |
| Contact Action Stimulus: |
| Increase |
| Thread Size: |
| 0.190 inches all threaded hole |
| Mounting Facility Pattern: |
| Two position in-line |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally open, momentary action |
| Terminal Type: |
| Tab w/screw |
| Contact Load Current Rating: |
| 20.0 amperes resistive load single voltage |

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

NSN 5930-00-185-5141

Thermostatic Switch - Page 2 of 2



Contact Adjustment Range:

-10.00/+50.00 actuation point degrees fahrenheit and -10.00 to 50.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point knob and external actuation point knob

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Frequency In Hertz:

60.0 single voltage

Media For Which Designed:

Gas

Style Designator:

Rectangular

Thread Series Designator:

Unf all threaded hole

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0