

View Online at <https://aerobasegroup.com/nsn/5930-00-185-8023>

Thread Class:

2a single pressure connection

Thread Length:

0.550 inches single pressure connection

Overall Length:

2.700 inches

Outside Diameter:

0.438 inches single connection

Body Length:

1.588 inches

Overall Diameter:

0.750 inches

Pressure Switch Type:

Gage

Width Across Flats:

0.750 inches

Operating Temperature Rating:

Between -65.0 degrees fahrenheit and 275.0 degrees fahrenheit

Mounting Method:

Inlet connection

Features Provided:

Electrical box connector

Contact Action Stimulus:

Increase

Proof Pressure:

3200.00 pounds per square inch

Thread Size:

0.438 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Sensing Element Burst Pressure:

4500.00 pounds per square inch

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

2.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point not adjustable and actuation point not adjustable

Contact Stimulus Rating:

750.00 actuation point pounds per square inch and 625.00 deactuation point pounds per square inch and 125.00 differential point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A048b0