

View Online at <https://aerobasegroup.com/nsn/5930-00-186-9892>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches

**Body Length:**

1.940 inches

**Body Width:**

0.687 inches

**Body Height:**

0.830 inches

**Unthreaded Mounting Hole Diameter:**

0.140 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.094 inches

**Actuator Height:**

0.045 inches

**Actuator Free Position Height:**

0.625 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally open, momentary action single switch unit

**Switch Release Force:**

4.0 ounces

**Switch Actuating Force:**

Between 7.0 ounces and 9.0 ounces

**Actuator Movement:**

0.012 pretravel inches and 0.005 overtravel inches

**Contact Load Current Rating At Maximum Rated Voltage:**

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Special Features:**

Contains one plastic reset plunger 0.250 in.Dia with reset characteristics for operating force; 2-10 Oz and overtravel; 0.015 in. Min; no movement differential is given

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0