## NSN 5930-00-187-2589

**Hazardous Locations/environmental Protection:** 

Rotary Switch - Page 1 of 2

Moisture proof

Overall Length:



View Online at https://aerobasegroup.com/nsn/5930-00-187-2589

0.800 inches
Shaft Diameter:
0.100 inches single actuator
Shaft Length:
0.040 inches single actuator
Overall Diameter:
0.350 inches
Individual Section Quantity:
1
Operating Tempurature Range:
-65.0/+125.0 degrees celsius
Switch Contact Basic Design:
Nonpile-up symmetrical
Pole Quantity:
1 single section rear
Throw Quantity:
6 single section rear
Mounting Method:
Printed circuit single mounting facility
Contact Voltage Rating In Volts:
28.0 dc at sea level
Shaft Flat/slot Angular Location:
90.0 degrees from contact position 1 single actuator
Switch Actuator Indexing Position Quantity:
6 single actuator
Shaft Type:
Round, slotted single actuator
Terminal Type:
Printed circuit
Contact Switching Action:
Breaks before makes single section rear
Switch Actuator Positioning Increment:
60.0 degrees single actuator
Contact Load Current Rating:
250.0 milliamperes resistive load dc at sea level
Style Designator:
Miniature, pin mount
Shelf Life:
N/a

## **NSN 5930-00-187-2589** Rotary Switch - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

Demilitarization:

No

Fiig:

A052b0