

View Online at <https://aerobasegroup.com/nsn/5930-00-188-4023>

Thread Class:

2a single mounting facility

Thread Length:

0.250 inches single mounting facility

Hazardous Locations/environmental Protection:

Dustproof

Overall Length:

2.096 inches

Overall Height:

1.750 inches

Overall Width:

1.375 inches

First Flat Length:

0.375 inches single actuator

Flat Height:

0.198 inches single actuator and 0.201 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.251 inches single actuator

Shaft Length:

0.437 inches single actuator

Nonturn Device Radius:

0.468 inches at 3:00 o'clock and 0.475 inches at 3:00 o'clock

Individual Section Quantity:

1

Nonturn Device Type:

Pin at 3:00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Features Provided:

Cam actuated

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

250.0 ac at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from nonturn device single actuator

Cam Actuated Switch Contact Arrangement:

1 two circuit, double break/double make, both positions maintained single switch single section rear

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, slotted, flatted single actuator

Terminal Type:

Quick disconnect, male

Contact Switching Action:

Breaks before makes single section rear

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

25.0 amperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0