NSN 5930-00-188-4031

Sensitive Switch - Page 1 of 1

A053a0



View Online at https://aerobasegroup.com/nsn/5930-00-188-4031

| Body Style: |
|--|
| Bushing/hole mounted |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.000 inches |
| Bushing Length: |
| 0.500 inches |
| Body Length: |
| 1.936 inches |
| Body Width: |
| 0.687 inches |
| Body Height: |
| 1.000 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.140 inches |
| Actuator Free Position Height: |
| 1.571 inches |
| Maximum Voltage Rating In Volts: |
| 250.0 ac and 230.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Nonpile-up Contact Arrangement: |
| 1 pole, double throw, one position momentary single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| 13.0 ounces |
| Actuator Movement: |
| Between 0.040 pretravel inches and 0.203 overtravel inches and 0.005 differential inches |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 200.000 milliamperes resistive dc and 50.000 milliamperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes motor ac |
| Terminal Type And Quantity: |
| 3 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |