NSN 5930-00-188-7795

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-188-7795 **Thread Class:** 2b **Body Style:** Hole mounted **Hazardous Locations/environmental Protection:** Dustproof and watertight **Overall Length:** 4.440 inches **Overall Height:** 1.780 inches **Overall Width:** 1.650 inches **Case Material:** Metal **Actuator Style:** Round **Actuator Free Position Height:** 1.600 inches **Housing Height:** 1.780 inches **Housing Length:** 2.840 inches **Housing Width:** 1.650 inches **Center To Center Distance Between Housing Mounting Facilities Parallel To Length:** 2.340 inches Center To Center Distance Between Housing Mounting Facilities Parallel To Width: 1.160 inches **Maximum Voltage Rating In Volts:** 440.0 ac and 355.0 dc **Inclosure Type:** Fully enclosed **Mounting Method:** Threaded hole **Features Provided:** Actuator seal **Thread Size:** 0.190 inches

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Actuating Force:

92.0 ounces

NSN 5930-00-188-7795

Sensitive Switch - Page 2 of 2



Actuator N	lovement
------------	----------

0.040 pretravel inches and 0.275 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 6.000 amperes resistive ac

Special Features:

Tw0 mounting holes threaded for rear mounting

Thread Series Designator:

Unf

Terminal Type And Quantity:

3 screw

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A053a0