

View Online at <https://aerobasegroup.com/nsn/5930-00-189-1480>

**Thread Class:**

2b all pressure connection

**Inside Diameter:**

0.125 inches all connections

**Overall Length:**

4.625 inches

**Overall Height:**

1.812 inches

**Overall Width:**

3.500 inches

**Body Diameter:**

3.500 inches

**Distance Between Mounting Facility Centers:**

4.250 inches

**Pressure Switch Type:**

Gage

**Mounting Method:**

Base

**Thready Qty Per Inch (tpi):**

20 all pressure connection

**Contact Action Stimulus:**

Increase

**Proof Pressure:**

5.00 pounds per square inch gage

**Thread Size:**

0.125 inches single pressure connection

**Mounting Facility Pattern:**

Two position in-line

**Nonpile-up Contact Arrangement:**

1 pole, double throw, both positions maintained

**Terminal Type:**

Tab w/screw

**Contact Load Current Rating:**

15.0 amperes resistive load single voltage

**Contact Adjustability:**

Deactuation point adjustable and actuation point adjustable

**Contact Adjustment Range:**

+0.15/+0.50 actuation point inches of water and +13.00 to 48.00 deactuation point inches of water

**Contact Adjustment Type:**

External deactuation point screw and external actuation point screw

**Contact Stimulus Rating:**

0.14 differential point inches of water

**Contact Voltage Rating In Volts:**

240.0 ac at sea level single voltage

**Pressure Connector Type:**

Plain, threaded internal all connections

**Media For Which Designed:**

Liquid

**Style Designator:**

Cylindrical w/lugs

**Thread Series Designator:**

Npt all pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A048b0