

View Online at <https://aerobasegroup.com/nsn/5930-00-189-1480>

Thread Class:

2b all pressure connection

Inside Diameter:

0.125 inches all connections

Overall Length:

4.625 inches

Overall Height:

1.812 inches

Overall Width:

3.500 inches

Body Diameter:

3.500 inches

Distance Between Mounting Facility Centers:

4.250 inches

Pressure Switch Type:

Gage

Mounting Method:

Base

Thready Qty Per Inch (tpi):

20 all pressure connection

Contact Action Stimulus:

Increase

Proof Pressure:

5.00 pounds per square inch gage

Thread Size:

0.125 inches single pressure connection

Mounting Facility Pattern:

Two position in-line

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Tab w/screw

Contact Load Current Rating:

15.0 amperes resistive load single voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+0.15/+0.50 actuation point inches of water and +13.00 to 48.00 deactuation point inches of water

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Stimulus Rating:

0.14 differential point inches of water

Contact Voltage Rating In Volts:

240.0 ac at sea level single voltage

Pressure Connector Type:

Plain, threaded internal all connections

Media For Which Designed:

Liquid

Style Designator:

Cylindrical w/lugs

Thread Series Designator:

Npt all pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0