# NSN 5930-00-189-1644

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-189-1644

### Body Style:

Panel mounted

#### Hazardous Locations/environmental Protection:

Explosion proof and humidity resistant

#### **Overall Length:**

3.096 inches

#### **Overall Height:**

0.750 inches

#### **Overall Width:**

0.750 inches

#### **Body Width:**

0.750 inches

#### **Body Height:**

0.750 inches

#### Case Material:

Metal

## Actuator Length:

0.620 inches

## Actuator Style:

Rectangular

## Actuator Height:

0.100 inches

#### Actuator Width:

0.620 inches

#### Actuator Color:

Black single actuator

#### **Illuminated Actuator Color:**

Green single actuator

#### **Actuator Inscription:**

On single actuator

#### Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

#### Mounting Surface To Terminal End Distance:

2.950 inches

#### Inclosure Type:

Fully enclosed

## **Mounting Method:**

Panel

#### **Features Provided:**

Full display lens

#### **Nonpile-up Contact Arrangement:**

2 two circuit, double make, two positions momentary single switch unit

NSN 5930-00-189-1644

Push Switch - Page 2 of 2



## Contact Load Current Rating At Maximum Rated Voltage:

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes

inductive ac and 1.000 amperes lamp ac

## **Precious Material And Location:**

Contacts silver

## Terminal Type And Quantity:

1 socket, integrated wire termination

Shelf Life:

N/a

Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

Fiig:

A053a0