## NSN 5930-00-189-1650

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-189-1650

Body Style:					
Panel mounted					
Hazardous Locations/environmental Protection:					
Explosion proof and humidity resistant					
Overall Length:					
3.560 inches					
Overall Height:					
0.750 inches					
Overall Width:					
0.750 inches					
Body Width:					
0.750 inches					
Body Height:					
0.750 inches					
Case Material:					
Metal					
Actuator Length:					
0.620 inches					
Actuator Style:					
Rectangular					
Actuator Height:					
0.100 inches					
Actuator Width:					
0.620 inches					
Actuator Color:					
Black single actuator					
Illuminated Actuator Color:					
Green and white single actuator					
Actuator Inscription:					
Hot ovrd single actuator					
Maximum Voltage Rating In Volts:					
115.0 ac and 28.0 dc					
Mounting Surface To Terminal End Distance:					
3.096 inches					
Inclosure Type:					
Fully enclosed					
Mounting Method:					
Panel					
Features Provided:					
Full display lens					
Nonpile-up Contact Arrangement:					
3 two circuit, double make, two positions momentary single switch unit					

## NSN 5930-00-189-1650

Push Switch - Page 2 of 2



## **Contact Load Current Rating At Maximum Rated Voltage:**

7.500 amperes resistive dc and 5.000 amperes inductive dc and 1.000 amperes lamp dc and 7.500 amperes resistive ac and 5.000 amperes inductive ac and 1.000 amperes lamp ac

Draci	ioue	Materi	ial ∆n≀	414	ocation:
- 1 せし	ıvus	IVIALEI	ıaı Alıv	a L	Juanion.

Contacts silver

## **Terminal Type And Quantity:**

1 socket, integrated wire termination

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0