

View Online at <https://aerobasegroup.com/nsn/5930-00-189-3659>

Thread Length:

0.360 inches single mounting facility and 0.390 inches single mounting facility

Overall Length:

3.514 inches

Overall Height:

Between 1.297 inches and 1.327 inches

Overall Width:

Between 1.110 inches and 1.140 inches

Shaft Diameter:

0.245 inches single actuator and 0.250 inches single actuator

Shaft Length:

1.391 inches single actuator and 1.421 inches single actuator

Nonturn Device Radius:

0.516 inches at 9: 00 o'clock and 0.546 inches at 9: 00 o'clock

Individual Section Quantity:

6

Nonturn Device Type:

Tab at 9: 00 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

10 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks, breaks before makes each section front

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load dc at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0