

View Online at <https://aerobasegroup.com/nsn/5930-00-189-3659>

**Thread Length:**

0.360 inches single mounting facility and 0.390 inches single mounting facility

**Overall Length:**

3.514 inches

**Overall Height:**

Between 1.297 inches and 1.327 inches

**Overall Width:**

Between 1.110 inches and 1.140 inches

**Shaft Diameter:**

0.245 inches single actuator and 0.250 inches single actuator

**Shaft Length:**

1.391 inches single actuator and 1.421 inches single actuator

**Nonturn Device Radius:**

0.516 inches at 9: 00 o'clock and 0.546 inches at 9: 00 o'clock

**Individual Section Quantity:**

6

**Nonturn Device Type:**

Tab at 9: 00 o'clock

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded bushing single mounting facility

**Thread Size:**

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Switch Actuator Indexing Position Quantity:**

10 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Tab, solder lug

**Contact Switching Action:**

Makes before breaks, breaks before makes each section front

**Switch Actuator Positioning Increment:**

30.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

1.0 amperes resistive load dc at sea level

**Precious Material And Location:**

Contacts silver

**Precious Material:**

Silver

**Style Designator:**

Circular wafer, bushing mount

**Thread Series Designator:**

Unef single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0