## NSN 5930-00-189-4427

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-189-4427 **Overall Height:** 2.094 inches **Overall Width:** 2.328 inches **Distance Between Mounting Facility Centers:** 2.562 inches **Capillary Tube Length:** 120.000 inches **Bulb Length:** 5.250 inches **Bulb Diameter:** 0.375 inches **Longest Horizontal Distance Between Mounting Centers:** 2.562 inches **Tempurature Sensing Element Type:** Capillary tube-bulb **Mounting Method: Bracket Contact Action Stimulus:** Increase **Mounting Facility Pattern:** Two position in-line **Nonpile-up Contact Arrangement:** 1 pole, single throw, normally closed, momentary action **Terminal Type:** Threaded stud **Contact Load Current Rating:** 30.0 amperes resistive load second voltage **Contact Adjustability:** Deactuation point adjustable and actuation point adjustable, preset **Contact Adjustment Range:** -10.00 to 55.00 actuation point degrees fahrenheit **Contact Adjustment Type:** External actuation point knob **Contact Stimulus Rating:** 6.00 differential point degrees fahrenheit **Contact Voltage Rating In Volts:** 277.0 ac at sea level first voltage Media For Which Designed:

Gas or liquid

**Style Designator:** 

Rectangular

## NSN 5930-00-189-4427

Thermostatic Switch - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0