NSN 5930-00-189-4670

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-189-4670

| Body Style: |
|---|
| Bushing mounted |
| Bushing Length: |
| Between 0.295 inches and 0.325 inches |
| Body Length: |
| 1.183 inches |
| Body Width: |
| 0.800 inches |
| Body Height: |
| 1.270 inches |
| Actuator Diameter: |
| Between 0.308 inches and 0.338 inches |
| Actuator Height: |
| 0.255 inches |
| Actuator Color: |
| Red single actuator |
| Maximum Voltage Rating In Volts: |
| 115.0 ac and 28.0 dc |
| Inclosure Type: |
| Uninclosed |
| Mounting Method: |
| Threaded bushing |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.469 inches |
| Nonpile-up Contact Arrangement: |
| 4 pole, double throw, both positions maintained single switch unit |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes |
| inductive ac and 1.500 amperes lamp ac |
| Test Data Document: |
| 81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Uns |
| Terminal Type And Quantity: |
| 12 turret |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

N

Demilitarization:

NSN 5930-00-189-4670

Push Switch - Page 2 of 2



Fiig:

A053a0