

View Online at <https://aerobasegroup.com/nsn/5930-00-189-4670>

Body Style:

Bushing mounted

Bushing Length:

Between 0.295 inches and 0.325 inches

Body Length:

1.183 inches

Body Width:

0.800 inches

Body Height:

1.270 inches

Actuator Diameter:

Between 0.308 inches and 0.338 inches

Actuator Height:

0.255 inches

Actuator Color:

Red single actuator

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Uninclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

4 pole, double throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 2.000 amperes lamp dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac and 1.500 amperes lamp ac

Test Data Document:

81349-mil-s-8805 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Uns

Terminal Type And Quantity:

12 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0