

View Online at <https://aerobasegroup.com/nsn/5930-00-189-8672>

Body Style:

Bushing mount

Hazardous Locations/environmental Protection:

Explosion proof

Body Diameter:

0.562 inches

Bushing Length:

Between 0.418 inches and 0.458 inches

Body Length:

0.581 inches

Switch Actuator Quantity:

1

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

Between 1.017 inches and 1.081 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in

Actuator Color:

Natural single actuator

Maximum Voltage Rating In Volts:

125.0 ac and 50.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Threaded bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

1 pole, single throw, both positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 1.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0