

View Online at <https://aerobasegroup.com/nsn/5930-00-189-8672>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Explosion proof

**Body Diameter:**

0.562 inches

**Bushing Length:**

Between 0.418 inches and 0.458 inches

**Body Length:**

0.581 inches

**Switch Actuator Quantity:**

1

**Actuator Style:**

Round

**Actuator Diameter:**

0.430 inches

**Actuator Height:**

Between 1.017 inches and 1.081 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in

**Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

125.0 ac and 50.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

1 pole, single throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

1.000 amperes resistive dc and 1.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0