NSN 5930-00-190-4762

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-190-4762

View Online at https://aerobasegroup.com/nsn/5930-00-190-4762
Overall Length:
2.781 inches
Overall Height:
2.219 inches
Overall Width:
1.500 inches
Longest Horizontal Distance Between Mounting Centers:
0.688 inches
Shortest Horizontal Distance Between Mounting Centers:
0.344 inches
Longest Vertical Distance Between Mounting Centers:
0.469 inches
Pressure Switch Type:
Gage
Mounting Method:
Base and threaded hole
Thready Qty Per Inch (tpi):
32 all threaded hole
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Isosceles triangle
Nonpile-up Contact Arrangement:
1 pole, single throw, normally open, momentary action
Terminal Type:
Quick disconnect, male
Contact Load Current Rating:
6.5 amperes resistive load second voltage
Contact Adjustability:
Deactuation point not adjustable and actuation point not adjustable
Contact Stimulus Rating:
37.00 actuation point pounds per square inch and 27.00 deactuation point pounds per square inch and 10.00 differential point pounds per
square inch
Contact Voltage Rating In Volts:
230.0 ac at sea level first voltage
Media For Which Designed:
Liquid Stulo Designator:
Style Designator: Rectangular
Shelf Life:
N/a
Unit Of Measure:
Unit United Suit.

NSN 5930-00-190-4762

Pressure Switch - Page 2 of 2

Demilitarization:

No

Fiig:

A048b0

