

View Online at <https://aerobasegroup.com/nsn/5930-00-190-4763>

**Thread Class:**

2b single mounting facility

**Overall Length:**

4.473 inches

**Overall Height:**

1.625 inches

**Overall Width:**

1.450 inches

**First Flat Length:**

0.750 inches single actuator

**Flat Height:**

0.218 inches single actuator

**Shaft Diameter:**

0.248 inches single actuator

**Shaft Length:**

1.000 inches single actuator

**Individual Section Quantity:**

7

**Longest Horizontal Distance Between Mounting Centers:**

1.000 inches single mounting facility

**Switch Contact Basic Design:**

Nonpile-up nonsymmetrical

**Mounting Method:**

Threaded hole single mounting facility

**Features Provided:**

Cam actuated

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.138 inches single mounting facility

**Contact Voltage Rating In Volts:**

28.0 dc at sea level

**Shaft Flat/slot Angular Location:**

180.0 degrees from contact position 1 single actuator

**Mounting Facility Pattern:**

Two position in-line single mounting facility

**Cam Actuated Switch Contact Arrangement:**

1 pole, double throw, one position momentary each switch each section in-line

**Switch Actuator Indexing Position Quantity:**

2 single actuator

**Shaft Type:**

Round, flatted single actuator

**Terminal Type:**

Tab w/screw

**Contact Switching Action:**

Makes before breaks, breaks before makes each section in-line

**Switch Actuator Positioning Increment:**

45.0 degrees single actuator

**Switch Actuator Stop Device Type:**

Fixed stop single actuator

**Contact Load Current Rating:**

10.0 amperes resistive load dc at sea level and 6.0 amperes inductive load dc at sea level and 6.0 amperes motor load dc at sea level

**Style Designator:**

In-line, cam actuated

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A052b0