

View Online at <https://aerobasegroup.com/nsn/5930-00-190-4763>

Thread Class:

2b single mounting facility

Overall Length:

4.473 inches

Overall Height:

1.625 inches

Overall Width:

1.450 inches

First Flat Length:

0.750 inches single actuator

Flat Height:

0.218 inches single actuator

Shaft Diameter:

0.248 inches single actuator

Shaft Length:

1.000 inches single actuator

Individual Section Quantity:

7

Longest Horizontal Distance Between Mounting Centers:

1.000 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded hole single mounting facility

Features Provided:

Cam actuated

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Shaft Flat/slot Angular Location:

180.0 degrees from contact position 1 single actuator

Mounting Facility Pattern:

Two position in-line single mounting facility

Cam Actuated Switch Contact Arrangement:

1 pole, double throw, one position momentary each switch each section in-line

Switch Actuator Indexing Position Quantity:

2 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab w/screw

Contact Switching Action:

Makes before breaks, breaks before makes each section in-line

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load dc at sea level and 6.0 amperes inductive load dc at sea level and 6.0 amperes motor load dc at sea level

Style Designator:

In-line, cam actuated

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0