

View Online at <https://aerobasegroup.com/nsn/5930-00-192-2839>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

Between 1.795 inches and 1.825 inches

Body Width:

Between 0.625 inches and 0.655 inches

Body Height:

Between 0.625 inches and 0.655 inches

Unthreaded Mounting Hole Diameter:

0.145 inches

Actuator Style:

Round

Actuator Diameter:

Between 0.245 inches and 0.255 inches

Actuator Height:

0.300 inches

Actuator Free Position Height:

Between 0.690 inches and 0.750 inches

Maximum Voltage Rating In Volts:

250.0 ac

Inclosure Type:

Fully enclosed

Nonpile-up Contact Arrangement:

1 pole, single throw, normally open, double make, momentary action single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.050 pretravel inches and 0.050 overtravel inches and 0.010 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive ac

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0